



Water Cut-Off Mastic Product Data

Water Cut-Off Mastic

Water Cut-Off Mastic is a one-component, low viscosity, self-wetting, butyl-blend mastic designed to be used in conjunction with roofing and waterproofing systems. It is primarily used as a sealing agent between various membranes and applicable when membrane is being terminated using a compression-type seal.

Water Cut-Off Mastic is an extremely tacky material and will remain as such when used with compression-type terminations.

Intended Uses

Water Cut-Off Mastic is primarily used as a sealing agent between various membranes and applicable when membrane is being terminated using a compression-type seal.

Features and Benefits

- Extremely tacky
- Provides a durable compression-type seal between various membranes and parapet wall constructions

Coverage Rate

3 linear metres per tube at the recommended application rate of at 11mm bead.



Application*

1. All surfaces to be sealed with Water Cut-Off Mastic must be free of moisture, oil, dirt and other foreign materials. Water Cut-Off Mastic cannot be used on insulation.
2. Apply an 11 mm bead of Water Cut-Off Mastic between the substrate and the edge of the membrane.
3. Apply appropriate termination material and secure to provide constant compression for the Water Cut-Off Mastic.

* REVIEW CURRENT RUBBERBOND SPECIFICATIONS AND DETAILS FOR SPECIFIC APPLICATION REQUIREMENTS.

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433





Water Cut-Off Mastic Product Data

Precautions

1. Review the applicable Material Safety Data Sheet for complete safety information prior to use.
2. Water Cut-Off Mastic is FLAMMABLE – It contains solvents that are dangerous fire and explosion hazards when exposed to heat, flame or sparks. Store and use away from all sources of heat, flame or sparks. Do not smoke while applying. Do not use in a confined or unventilated area. Vapours are heavier than air and may travel along ground to a distant ignition source and flash back. A red caution label is required when shipping.
3. Avoid breathing vapours. Keep container closed when not in use. Use with adequate ventilation. If inhaled, remove to fresh air. If not breathing, perform artificial respiration. If breathing is difficult, give oxygen. Call a physician immediately.
4. If swallowed, DO NOT INDUCE VOMITING. Call a physician immediately.
5. Avoid contact with eyes. Safety glasses or goggles are recommended. If splashed in eyes, immediately flush eyes with plenty of clean water for at least 15 minutes. Contact a physician immediately.
6. Avoid contact with skin. Wash hands thoroughly after handling. In case of contact with skin, thoroughly wash affected area with soap and water. Note: Permeation-resistant gloves are recommended to be worn when using this product to protect hands from irritating ingredients.

RubberBond Water Cut-Off Mastic	
Typical Properties & Characteristics*	
Solids	80%
Colour	Grey
Flash Point	4° C Closed Cup
Service Temperature	-40°C to 93°C
Specific Gravity	1.29
Cold Weather Flex	Excellent
Viscosity	1,320,000 Cps
V.O.C	250 grams/litre
Clean Up	Weathered Membrane Cleaner
Shelf life	1 year, unopened container
Coverage	3 linear metre per tube

* Typical properties and characteristics are based on samples tested and are not guaranteed for all samples of this product. This data and information is intended as a guide and does not reflect the specification or specification range for any particular property of this product.

Before using this product please ensure that you have been supplied with and have read carefully the following information:

1. The product labels
2. RubberBond Water Cut-Off Mastic Material Safety Data Sheet

Exclusive British Isles Distributors for Carlisle-SynTec and RubberBond EPDM single ply roofing materials.

Flex-R Ltd, Sandswood House, Hillbottom Road, Sands Industrial Estate, High Wycombe, Bucks ,HP12 4HJ. Tel: +44 (0)1494 448792 Fax: +44 (0)1494 858433

