SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING 1.1 Product identifier: 10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

Other means of identification:

Not relevant

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses (Professional users): Adhesive For Professional users only. Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

RubberBond Sandswood House, Hillbottom Road, Sands Industrial Estate, HP12 4HJ High Wycombe - Buckinghamshire - United Kingdom Phone: +44 (0) 1494 448 792 enq@rubberbond.co.uk www.rubberbond.co.uk/

1.4 Emergency telephone number: +44 (0) 1494 448792 (Monday-Thursday 8.30am-5.30pm, 9.30am - 4.30pm Friday GMT)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Classification of this product has been carried out in accordance with GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567).

Aerosol 1: Flammable aerosols, Category 1, H222 Aerosol 1: Pressurised container: May burst if heated., H229 Aquatic Chronic 2: Hazardous to the aquatic environment, long-term hazard, Category 2, H411 Eye Irrit. 2: Eye irritation, Category 2, H319 Skin Irrit. 2: Skin irritation, Category 2, H315 STOT SE 3: Specific toxicity causing drowsiness and dizziness, single exposure, Category 3, H336

2.2 Label elements:

GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):

Danger



Hazard statements:

Aerosol 1: H222 - Extremely flammable aerosol. Aerosol 1: H229 - Pressurised container: May burst if heated. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects. Eye Irrit. 2: H319 - Causes serious eye irritation. Skin Irrit. 2: H315 - Causes skin irritation. STOT SE 3: H336 - May cause drowsiness or dizziness. **Precautionary statements:**



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SECTION 2: HAZARDS IDENTIFICATION (continued) P210: Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211: Do not spray on an open flame or other ignition source. P251: Do not pierce or burn, even after use. P261: Avoid breathing spray P264: Wash thoroughly after handling P271: Use only outdoors or in a well-ventilated area. P273: Avoid release to the environment. P280: Wear protective gloves/protective clothing/respiratory protection/eye protection/protective footwear. P302+P352: IF ON SKIN: Wash with plenty of soap and water. P304+P340: IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing P312: Call a POISON CENTER or doctor/physician if you feel unwell. P332+P313: If skin irritation occurs: Get medical advice/attention. P337+P313: If eye irritation persists: Get medical advice/attention. P362+P364: Take off contaminated clothing and wash it before reuse. P391: Collect spillage. P403+P233: Store in a well-ventilated place. Keep container tightly closed. P405: Store locked up. P410+P412: Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. P501: Dispose of the contents and/or its container in line with regulations on dangerous waste or packaging and waste packaging respectively. Supplementary information: EUH208: Contains tris(nonylphenyl) phosphite. May produce an allergic reaction.

Substances that contribute to the classification

Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane; acetone (CAS: 67-64-1); Butanone (CAS: 78-93-3)

2.3 Other hazards:

Product does not meet PBT/vPvB criteria

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Not relevant

3.2 Mixture:

Chemical description: Mixture of substances

Components:

In accordance with Annex II of The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020, the product contains:

	Identification	Chemical name/Classification	Concentration
CAS: EC: REACH:	115-10-6 204-065-8 01-2119472128-37- XXXX	Dimethyl ether Flam. Gas 1A: H220; Press. Gas: H280 - Danger	40 - <50 %
CAS: EC: REACH:	Not relevant 921-024-6 01-2119475514-35- XXXX	Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane Aquatic Chronic 2: H411; Asp. Tox. 1: H304; Flam. Liq. 2: H225; Skin Irrit. 2: H315; STOT SE 3: H336 🔶 🚺 🍪 🏠 - Danger	20 - <30 %
CAS: EC: REACH:	67-64-1 200-662-2 01-2119471330-49- XXXX	acetone Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	5 - <10 %
CAS: EC: REACH:	78-93-3 201-159-0 01-2119457290-43- XXXX	Butanone Eye Irrit. 2: H319; Flam. Liq. 2: H225; STOT SE 3: H336; EUH066 - Danger	5 - <10 %
CAS: EC: REACH:	26523-78-4 247-759-6 01-2119520601-54- XXXX	tris(nonylphenyl) phosphite Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning	0.1 - <1 %
CAS: EC: REACH:	14726-36-4 238-778-0 01-2119543708-31- XXXX	Zinc bis(dibenzyldithiocarbamate)	0.1 - <1 %



SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply,etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Foam extinguisher (AB), Dry Chemical Powder (ABC) Fire Extinguisher, Carbon dioxide extinguisher (BC)

Unsuitable extinguishing media:

Water jet

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and Self Contained Breathing Apparatus. Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:



SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground. **For emergency responders:**

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Prevent the entrance of product in drains, sewers or watercourses. Absorb the spill using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. Collect the product in appropriate containers and manage it according to current legislation.

Spillages in water or sea:

Small spillages:

Contain spillage using barriers or similar equipment. Use suitable absorbents for collection and treat the waste in accordance with current regulations.

Large spillages:

If possible, contain spillage in open water using barriers or similar equipment. If this is not possible, try to control its spread and collect the product with suitable mechanical means. Always consult experts before using dispersants and make sure you have the necessary approvals if they are to be used. Treat the waste according to current regulations.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

Store in a cool, dry, well-ventilated location

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

Other information:

Storage Temperature: Between 5°C and 25°C

7.3 Specific end use(s):

See Section 1.2

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

8.1 Control parameters:

Substances whose occupational exposure limits have to be assessed in the workplace:

EH40/2005 Workplace exposure limits, fourth edition, published 2020:

Identification	Occupa	ational exposure li	mits
Dimethyl ether	WEL (8h)	400 ppm	766 mg/m ³
CAS: 115-10-6	WEL (15 min)	500 ppm	958 mg/m ³
acetone	WEL (8h)	500 ppm	1210 mg/m ³
CAS: 67-64-1	WEL (15 min)	1500 ppm	3620 mg/m ³
Butanone	WEL (8h)	200 ppm	600 mg/m ³
CAS: 78-93-3	WEL (15 min)	300 ppm	899 mg/m ³

Biological limit values:

BIOLOGICAL MONITORING GUIDANCE VALUES (BMGVS) - EH40/2005

Identification	NULL	NULL	NULL
Butanone CAS: 78-93-3	5 mg/L	Butan-2-one in urine	Post shift

DNEL (Workers):

		Short e	exposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	1894 mg/m ³	Not relevant
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: Not relevant	Dermal	Not relevant	Not relevant	773 mg/kg	Not relevant
EC: 921-024-6	Inhalation	Not relevant	Not relevant	2035 mg/m³	Not relevant
acetone	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 67-64-1	Dermal	Not relevant	Not relevant	186 mg/kg	Not relevant
EC: 200-662-2	Inhalation	Not relevant	2420 mg/m ³	1210 mg/m ³	Not relevant
Butanone	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 78-93-3	Dermal	Not relevant	Not relevant	1161 mg/kg	Not relevant
EC: 201-159-0	Inhalation	Not relevant	Not relevant	600 mg/m³	Not relevant
tris(nonylphenyl) phosphite	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 26523-78-4	Dermal	Not relevant	Not relevant	16.7 mg/kg	Not relevant
EC: 247-759-6	Inhalation	Not relevant	Not relevant	23.6 mg/m ³	Not relevant
Zinc bis(dibenzyldithiocarbamate)	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 14726-36-4	Dermal	Not relevant	Not relevant	1000 mg/kg	Not relevant
EC: 238-778-0	Inhalation	Not relevant	Not relevant	7 mg/m ³	Not relevant

DNEL (General population):

		Short e	xposure	Long e	xposure
Identification		Systemic	Local	Systemic	Local
Dimethyl ether	Oral	Not relevant	Not relevant	Not relevant	Not relevant
CAS: 115-10-6	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
EC: 204-065-8	Inhalation	Not relevant	Not relevant	471 mg/m³	Not relevant
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	Oral	Not relevant	Not relevant	699 mg/kg	Not relevant
CAS: Not relevant	Dermal	Not relevant	Not relevant	699 mg/kg	Not relevant
EC: 921-024-6	Inhalation	Not relevant	Not relevant	608 mg/m³	Not relevant
acetone	Oral	Not relevant	Not relevant	62 mg/kg	Not relevant
CAS: 67-64-1	Dermal	Not relevant	Not relevant	62 mg/kg	Not relevant
EC: 200-662-2	Inhalation	Not relevant	Not relevant	200 mg/m³	Not relevant
Butanone	Oral	Not relevant	Not relevant	31 mg/kg	Not relevant
CAS: 78-93-3	Dermal	Not relevant	Not relevant	412 mg/kg	Not relevant
EC: 201-159-0	Inhalation	Not relevant	Not relevant	106 mg/m³	Not relevant



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

			· · · · ·		
		Short	exposure	Lo	ng exposure
Identification		Systemic	Local	Systemic	Local
tris(nonylphenyl) phosphite	Oral	Not relevant	Not relevant	1.67 mg/kg	Not relevant
CAS: 26523-78-4	Dermal	Not relevant	Not relevant	8.35 mg/kg	Not relevant
EC: 247-759-6	Inhalation	Not relevant	Not relevant	11.8 mg/m ³	Not relevant
Zinc bis(dibenzyldithiocarbamate)	Oral	Not relevant	Not relevant	1 mg/kg	Not relevant
CAS: 14726-36-4	Dermal	Not relevant	Not relevant	600 mg/kg	Not relevant
EC: 238-778-0	Inhalation	Not relevant	Not relevant	2 mg/m³	Not relevant
PNEC:					
Identification					
Dimethyl ether	STP	160 mg/L	Fresh water		0.155 mg/L
CAS: 115-10-6	Soil	0.045 mg/kg	Marine water		0.016 mg/L
EC: 204-065-8	Intermittent	1.549 mg/L	Sediment (Fresh	water)	0.681 mg/kg
	Oral	Not relevant	Sediment (Marine	e water)	0.069 mg/kg
acetone	STP	100 mg/L	Fresh water		10.6 mg/L
CAS: 67-64-1	Soil	29.5 mg/kg	Marine water		1.06 mg/L
EC: 200-662-2	Intermittent	21 mg/L	Sediment (Fresh	water)	30.4 mg/kg
	Oral	Not relevant	Sediment (Marine	e water)	3.04 mg/kg
Butanone	STP	709 mg/L	Fresh water		55.8 mg/L
CAS: 78-93-3	Soil	22.5 mg/kg	Marine water		55.8 mg/L
EC: 201-159-0	Intermittent	55.8 mg/L	Sediment (Fresh	water)	284.74 mg/kg
	Oral	1 g/kg	Sediment (Marine	e water)	284.7 mg/kg
tris(nonylphenyl) phosphite	STP	1.8 mg/L	Fresh water		0.05 mg/L
CAS: 26523-78-4	Soil	Not relevant	Marine water		0.05 mg/L
EC: 247-759-6	Intermittent	0.05 mg/L	Sediment (Fresh	water)	0.15 mg/kg
	Oral	0.037 g/kg	Sediment (Marine	e water)	0.15 mg/kg
Zinc bis(dibenzyldithiocarbamate)	STP	100 mg/L	Fresh water		Not relevant
CAS: 14726-36-4	Soil	Not relevant	Marine water		Not relevant
EC: 238-778-0	Intermittent	Not relevant	Sediment (Fresh	water)	Not relevant
	Oral	0.00456 g/kg	Sediment (Marine	e water)	Not relevant

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<UKCA marking>> or <<CE marking>>. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Remarks
Mandatory respiratory tract protection	Filter mask for gases, vapours and particles	Replace when an increase in resistence to breathing is observed and/or a smell or taste of the contaminant is detected.

C - Specific protection for the hands

Pictogram	PPE	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low -density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	Replace the gloves at any sign of deterioration.
	a mixture of several substances, the res	istance of the glove material can not be calculated in advance with

total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SECTION 8: EXPOSUR	E CONTROLS/PERSONAL PF	ROTECTION	l (continued)	
Pictogram	PPE		F	Remarks
Mandatory face protection	Panoramic glasses against splash/projectio	ns. Clean daily		according to the manufacturer's instructions. is a risk of splashing.
E Body protection				
Pictogram	PPE		F	Remarks
Mandatory complete body protection	Antistatic and fireproof protective clothing	1	Limited prote	ection against flames.
Mandatory foot protection	Safety footwear with antistatic and heat resistant properties		Replace boots at	any sign of deterioration.
F Additional emerge	ency measures			
It is advised to imp situations where r	plement additional emergency equip isk assessments highlight the neces	ments in workp sity of such eq	places that are partic uipments.	ularly exposed to the product or in
Emergency mea	sure Standards	E	Emergency measure	Standards
Emergency sho	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4	ł:2011	Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
	ormation, please refer to subsection 5 c Compounds in Paints, Varnishes 99.5 % weight 20 °C: Not relevant		Refinishing Produc	ts Regulations 2012:
SECTION 9: PHYSICAL	AND CHEMICAL PROPERTIE	ES		
9.1 Information on basic	c physical and chemical properties	5:		
For complete information	tion see the product datasheet.			
Appearance:				
Physical state at 20 %	C: A	erosol		
Appearance:	Ν	ot relevant *		
Colour:	G	ireen		
Odour:	C	haracteristic		
Odour threshold:	Ν	ot relevant *		
Volatility:				
Boiling point at atmos	pheric pressure: N	ot relevant *		
Vapour pressure at 20	0 °C: N	ot relevant *		
Vapour pressure at 50	0 °C: <	300000 Pa(3	00 kPa)	
Evaporation rate at 20	0 °C: N	ot relevant *		
Product description	:			
Density at 20 °C:	Ν	ot relevant *		
Relative density at 20	0 °C: 0	.82		
*Not relevant due to the na	ature of the product, not providing information	n property of its ha	azards.	

10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SEC	TION 9: PHYSICAL AND CHEMICAL PROPER	RTIES (continued)
	Dynamic viscosity at 20 ºC:	Not relevant *
	Kinematic viscosity at 20 °C:	Not relevant *
	Kinematic viscosity at 40 °C:	<20.5 mm²/s
	Concentration:	Not relevant *
	pH:	Not relevant *
	Vapour density at 20 °C:	Not relevant *
	Partition coefficient n-octanol/water 20 °C:	Not relevant *
	Solubility in water at 20 °C:	Not relevant *
	Solubility properties:	Not relevant *
	Decomposition temperature:	Not relevant *
	Melting point/freezing point:	Not relevant *
	Recipient pressure:	Not relevant *
	Flammability:	
	Flash Point:	-41 °C (Propellant)
	Flammability (solid, gas):	Not relevant *
	Autoignition temperature:	Not relevant *
	Lower flammability limit:	Not relevant *
	Upper flammability limit:	Not relevant *
	Particle characteristics:	
	Median equivalent diameter:	Not relevant *
9.2	Other information:	
	Information with regard to physical hazard classes	s:
	Explosive properties:	Not relevant *
	Oxidising properties:	Not relevant *
	Corrosive to metals:	Not relevant *
	Heat of combustion:	Not relevant *
	Aerosols-total percentage (by mass) of flammable components:	Not relevant *
	Other safety characteristics:	
	Surface tension at 20 °C:	Not relevant *
	Refraction index:	Not relevant *
	*Not relevant due to the nature of the product, not providing inform	nation property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Precaution	Precaution	Risk of combustion	Avoid direct impact	Not applicable

10.5 Incompatible materials:



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

Se co co CTIO .1 Inf Cc are Da In ad A-	omplex mixtures of chemica ompounds. DN 11: TOXICOLOGIC formation on toxicologic the experimental information ontains glycols. It is recom- re hazardous to the health angerous health implicat case of exposure that is re- dverse effects on health ma- - Ingestion (acute effect):	AL INFORMATION al effects: n related to the toxicolo mended not to breathe ions:	ogical properties of the proc e the vapours for prolonged at concentrations higher th	2), carbon monoxide and	other organic
Se co co CTIO .1 Inf Cc are Da In ad A-	ee subsection 10.3, 10.4 and omplex mixtures of chemical ompounds. DN 11: TOXICOLOGIC formation on toxicologic formation on toxicologic ne experimental information ontains glycols. It is recom- re hazardous to the health angerous health implicat case of exposure that is re- dverse effects on health ma- logestion (acute effect): - Acute toxicity: Based of	AL INFORMATION al effects: n related to the toxicolo mended not to breathe ions:	leased: carbon dioxide (CO) ogical properties of the proc e the vapours for prolonged at concentrations higher th	2), carbon monoxide and	other organic
COI COI COI COI Th CCC COI COI COI COI COI COI COI COI COI	omplex mixtures of chemica ompounds. ON 11: TOXICOLOGIC formation on toxicologic ne experimental information ontains glycols. It is recom- re hazardous to the health angerous health implicat case of exposure that is re- dverse effects on health ma- logestion (acute effect): - Acute toxicity: Based of	al substances can be rel AL INFORMATION al effects: In related to the toxicolo Immended not to breather ions: epetitive, prolonged or a	leased: carbon dioxide (CO) ogical properties of the proc e the vapours for prolonged at concentrations higher th	2), carbon monoxide and	other organic
.1 Inf Th Cc are Da In ad A-	formation on toxicologic ne experimental information ontains glycols. It is recom re hazardous to the health angerous health implicat case of exposure that is re dverse effects on health ma - Ingestion (acute effect): - Acute toxicity: Based of	al effects: n related to the toxicolo mended not to breathe ions: epetitive, prolonged or a	ogical properties of the proc e the vapours for prolonged at concentrations higher th		
Th Cc are Da In ad A-	ne experimental information ontains glycols. It is recom re hazardous to the health angerous health implicat case of exposure that is re dverse effects on health ma - Ingestion (acute effect): - Acute toxicity: Based of	n related to the toxicolo mended not to breathe ions: epetitive, prolonged or a	e the vapours for prolonged at concentrations higher th		
Co are Da In ad A-	ontains glycols. It is recom re hazardous to the health angerous health implicat case of exposure that is re dverse effects on health ma - Ingestion (acute effect): - Acute toxicity: Based of	imended not to breathe ions: epetitive, prolonged or a	e the vapours for prolonged at concentrations higher th		
are Da In ad A-	e hazardous to the health angerous health implicat case of exposure that is re dverse effects on health ma - Ingestion (acute effect): - Acute toxicity: Based of	ions: epetitive, prolonged or a	at concentrations higher th	l periods of time due to th	ne possibility of effects the
ad A-	 dverse effects on health ma Ingestion (acute effect): Acute toxicity: Based of 				
	- Acute toxicity: Based of			an the recommended occ	cupational exposure limit
5	 Corrosivity/Irritability: ⁻ and vomiting. Inhalation (acute effect): 	on. For more information	classification criteria are not on see section 3 considerable dose can caus		
C-	 Acute toxicity : Based as hazardous for inhalati Corrosivity/Irritability: I 	on. For more information Based on available data for this effect. For more	a, the classification criteria information see section 3.	are not met, as it does no	
D-	 Contact with the skin: Contact with the eyes: CMR effects (carcinogen 	Produces eye damage	e after contact.		
	as hazardous for the effe IARC: Not relevant	ects mentioned. For mo	e classification criteria are r re information see section lassification criteria are not	3.	
F-	hazardous for this effect. - Reproductive toxicity:	For more information s Based on available dat		are not met, as it does n	
	 Respiratory: Based on hazardous with sensitisir Skin: Based on availal dangerous with sensitisir 	ng effects. For more info ble data, the classificat ng effects. For more info	ion criteria are not met. Ho ormation see section 3.		
F-	 Specific target organ toxi Exposure in high concent 		posure: th the central nervous syste	am causing beadacha, di	zziness vertigo nausoo
G-	vomiting, confusion, and Specific target organ toxi	in serious cases, loss	of consciousness.	ausing neadable, di	Leness, verugo, nausea,
H-	it does not contain substa - Skin: Based on availal	ances classified as haz ble data, the classificat	ed exposure: Based on avai zardous for this effect. For r ion criteria are not met. Ho ure. For more information s	more information see sectore se	tion 3.



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Not relevant

Specific toxicology information on the substances:

Identification	Acute	toxicity	Genus
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	LD50 oral	5840 mg/kg	Rat
CAS: Not relevant	LD50 dermal	2920 mg/kg	Rat
EC: 921-024-6	LC50 inhalation vapour	>20 mg/L	
Dimethyl ether	LD50 oral	>2000 mg/kg	
CAS: 115-10-6 EC: 204-065-8	LD50 dermal	>2000 mg/kg	
EC: 204-000-8	LC50 inhalation gases	164000 ppm (4 h)	Rat
	LC50 inhalation mist	164000 ppm (4 h)	
acetone	LD50 oral	5800 mg/kg	Rat
CAS: 67-64-1	LD50 dermal	7426 mg/kg	Rabbit
EC: 200-662-2	LC50 inhalation vapour	76 mg/L (4 h)	Rat
Butanone	LD50 oral	4000 mg/kg	Rat
CAS: 78-93-3	LD50 dermal	6400 mg/kg	Rabbit
EC: 201-159-0	LC50 inhalation vapour	23.5 mg/L (4 h)	Rat
tris(nonylphenyl) phosphite	LD50 oral	>2000 mg/kg	
CAS: 26523-78-4	LD50 dermal	>2000 mg/kg	
EC: 247-759-6	LC50 inhalation dust	>5 mg/L	
Zinc bis(dibenzyldithiocarbamate)	LD50 oral	>5000 mg/kg	Rat
CAS: 14726-36-4	LD50 dermal	>2000 mg/kg	
EC: 238-778-0	LC50 inhalation dust	>5 mg/L	

Acute Toxicity Estimate (ATE mix):

	ATE mix	Ingredient(s) of unknown toxicity
Oral	>2000 mg/kg (Calculation method)	0 %
Dermal	>2000 mg/kg (Calculation method)	0 %
LC50 inhalation mist	>5 mg/L (4 h) (Calculation method)	0 %

Only the physical form mist can occur during any reasonably expected use of the product, including when the product is used to produce a new product.

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Toxic to aquatic life with long lasting effects.

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	LC50	5.1 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: Not relevant	EC50	Not relevant			
	EC50	Not relevant			
acetone	LC50	5540 mg/L (96 h)	Oncorhynchus mykiss	Fish	
CAS: 67-64-1	EC50	8800 mg/L (48 h)	Daphnia pulex	Crustacean	
	EC50	3400 mg/L (48 h)	Chlorella pyrenoidosa	Algae	
Butanone	LC50	3220 mg/L (96 h)	Pimephales promelas	Fish	
CAS: 78-93-3	EC50	5091 mg/L (48 h)	Daphnia magna	Crustacean	
	EC50	4300 mg/L (168 h)	Scenedesmus quadricauda	Algae	
tris(nonylphenyl) phosphite	LC50	>0.1 - 1 mg/L (96 h)		Fish	
CAS: 26523-78-4	EC50	>0.1 - 1 mg/L (48 h)		Crustacean	
	EC50	>0.1 - 1 mg/L (72 h)		Algae	



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

TION 12: ECOLOGICAL INFORMATION (co	ontinued)						
Identification		Concentration		Species		Genus	
Zinc bis(dibenzyldithiocarbamate)	LC50	Not relevant					
CAS: 14726-36-4	EC50	0.74 mg/L (48 h)		Daphnia magna		Crustacean	
	EC50	Not relevant					
Chronic toxicity:							
Identification		Concentration		Species		Genus	
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane	NOEC	Not relevant					
CAS: Not relevant	NOEC	0.17 mg/L		Daphnia magna		Crustacear	
acetone	NOEC	Not relevant	Not relevant				
CAS: 67-64-1	NOEC	2212 mg/L Daphnia		Daphnia magna		Crustacear	
Zinc bis(dibenzyldithiocarbamate)		0.1 mg/L		Danio rerio		Fish	
CAS: 14726-36-4	NOEC	0.0169 mg/L Daphnia magna			Crustacear		
Persistence and degradability:							
Substance-specific information:							
Identification	D	egradability		Biodegradat	oility		
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	BOD5	Not relevant	Conce	ntration	Not rele	evant	
CAS: Not relevant	COD	Not relevant	Period		28 days	;	
EC: 921-024-6	BOD5/COD	Not relevant	% Bioc	legradable	98 %		
acetone	BOD5	Not relevant	Conce	ntration	100 mg	/L	
CAS: 67-64-1	COD	Not relevant Period		eriod 28 day		days	
EC: 200-662-2	BOD5/COD	Not relevant	% Bioc	legradable	96 %		

EC: 201-159-0 12.3 Bioaccumulative potential:

Butanone

CAS: 78-93-3

Substance-specific information:

lde	entification	Bioaccumulation potential		
acetone		BCF	1	
CAS: 67-64-1		Pow Log	-0.24	
EC: 200-662-2		Potential	Low	
Butanone		BCF	3	
CAS: 78-93-3		Pow Log	0.29	
EC: 201-159-0		Potential	Low	

2.03 g O2/g

2.31 g O2/g

0.88

Concentration

% Biodegradable

Period

Not relevant

20 days

89 %

BOD5

COD

BOD5/COD

12.4 Mobility in soil:

Identification	Absorp	otion/desorption		Volatility
Dimethyl ether	Кос	Not relevant	Henry	Not relevant
CAS: 115-10-6	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	1.136E-2 N/m (25 °C)	Moist soil	Not relevant
acetone	Кос	1	Henry	2.93 Pa⋅m³/mol
CAS: 67-64-1	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.304E-2 N/m (25 °C)	Moist soil	Yes
Butanone	Кос	30	Henry	5.77 Pa⋅m³/mol
CAS: 78-93-3	Conclusion	Very High	Dry soil	Yes
	Surface tension	2.396E-2 N/m (25 °C)	Moist soil	Yes
Zinc bis(dibenzyldithiocarbamate)	Koc	2622000000	Henry	Not relevant
CAS: 14726-36-4	Conclusion	Immobile	Dry soil	Not relevant
	Surface tension	Not relevant	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Other adverse effects:

Not described



SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Coc	de	Description	Waste class
08 04	1 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste:

HP14 Ecotoxic, HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP3 Flammable, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance The Waste (England & Wales) Regulations 2011, 2011 No. 988. As under 15 01 of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of UK REACH the provisions related to waste management are stated:

UK legislation: The Waste (England & Wales) Regulations 2011.

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

with regard to A	DR 202	23 and RID 2023:	
	14.1	UN number:	UN3501
	14.2	UN proper shipping name:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Dimethyl ether; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
	14.3	Transport hazard class(es):	2
		Labels:	2.1
	14.4	Packing group:	N/A
		Environmental hazards: Special precautions for user	Yes
		Tunnel restriction code:	B/D
		Physico-Chemical properties:	see section 9
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant
Transport of dar	ngerou	is goods by sea:	
With regard to IM	DG 41	-22:	
	14.1	UN number:	UN3501
	14.2	UN proper shipping name:	CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Dimethyl ether; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane)
	14.3	Transport hazard class(es):	2.1
• •		Labels:	2.1
	14.4	Packing group:	N/A
	14.5	Marine pollutant:	Yes
	14.6	Special precautions for user	
		Special regulations:	274, 362
		EmS Codes:	F-H, S-Q
		Physico-Chemical properties:	see section 9
		Limited quantities:	0
		Segregation group:	Not relevant
	14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant
Transport of dar	ngerou	is goods by air:	
With regard to IA	TA/ICA	O 2025:	

With regard to IATA/ICAO 2025:



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SECTION 14: TRANSPOR	T INFORMATION (continued)	
14.1	UN number: UN proper shipping name:	UN3501 CHEMICAL UNDER PRESSURE, FLAMMABLE, N.O.S. (Dimethyl ether; Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n- hexane)
14.3	Transport hazard class(es): Labels:	2.1 2.1
14.4	Packing group:	N/A
14.5	Environmental hazards:	Yes
14.6	Special precautions for user	
	Physico-Chemical properties:	see section 9
14.7	Transport in bulk according to Annex II of Marpol and the IBC Code:	Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Substances listed in UK candidate list of substances of very high concern (SVHCs): *tris(nonylphenyl) phosphite (26523-78-4)* - Substances listed in UK REACH Authorisation List (Annex 14): Not relevant

Section	Description	Lower-tier requirements	Upper-tier requirements
P3a	FLAMMABLE AEROSOLS	150	500
E2	ENVIRONMENTAL HAZARDS	200	500

Restrictions to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII UK REACH, etc):

Regulation (EU) 2019/1148 on the marketing and use of explosives precursors: Contains acetone. Product under the provisions of Article 9. However, products that contain explosives precursors only to such a small extent and in such complex mixtures that the extraction of the explosives precursors is technically extremely difficult should be excluded from the scope of this Regulation. Shall not be used in:

---ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,

-tricks and jokes,

-games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

The Chemicals (Health and Safety) and Genetically Modified Organisms (Contained Use) (Amendment etc.) (EU Exit) Regulations 2020.

Control of Substances Hazardous to Health Regulations 2002 (as amended)

EH40/2005 Workplace exposure limits.

The Aerosol Dispensers Regulations 2009

The Product Safety and Metrology etc. (Amendment etc.) (EU Exit) Regulations 2019: SCHEDULE 13 -Amendment of the Aerosol Dispensers Regulations 2009

The Product Safety and Metrology etc. (Amendment etc.) (UK(NI) Indication) (EU Exit) Regulations 2020

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

This safety data sheet has been designed in accordance with ANNEX II-The REACH etc. (Amendment etc.) (EU Exit) Regulations 2020.

Texts of the legislative phrases mentioned in section 2:



10721786 - RubberBond Sprayable Bonding Adhesive 22L Canister

SEC	CTION 16: OTHER INFORMATION (continued)
	H315: Causes skin irritation.
	H336: May cause drowsiness or dizziness.
	H411: Toxic to aquatic life with long lasting effects.
	H222: Extremely flammable aerosol.
	H229: Pressurised container: May burst if heated.
	H319: Causes serious eye irritation.
	Texts of the legislative phrases mentioned in section 3:
	The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3
	GB CLP Regulation (UK S.I. 2019/720 and UK S.I. 2020/1567):
	Aquatic Acute 1: H400 - Very toxic to aquatic life.
	Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects.
	Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.
	Asp. Tox. 1: H304 - May be fatal if swallowed and enters airways.
	Eye Irrit. 2: H319 - Causes serious eye irritation.
	Flam. Gas 1A: H220 - Extremely flammable gas.
	Flam. Liq. 2: H225 - Highly flammable liquid and vapour.
	Press. Gas: H280 - Contains gas under pressure, may explode if heated. Skin Irrit. 2: H315 - Causes skin irritation.
	Skin Sens. 1: H317 - May cause an allergic skin reaction.
	STOT SE 3: H336 - May cause drowsiness or dizziness.
	Classification procedure:
	Skin Irrit. 2: Calculation method
	STOT SE 3: Calculation method
	Aquatic Chronic 2: Calculation method
	Aerosol 1: Calculation method
	Aerosol 1: Calculation method
	Eye Irrit. 2: Calculation method
	Advice related to training:
	Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.
	Principal bibliographical sources:
	http://echa.europa.eu
	http://eur-lex.europa.eu
	Abbreviations and acronyms:
	ADR: European agreement concerning the international carriage of dangerous goods by road
	IMDG: International maritime dangerous goods code
	IATA: International Air Transport Association
	ICAO: International Civil Aviation Organisation
	COD: Chemical Oxygen Demand
	BOD5: 5day biochemical oxygen demand
	BCF: Bioconcentration factor LD50: Lethal Dose 50
	LC50: Lethal Concentration 50
	EC50: Effective concentration 50
	LogPOW: Octanolwater partition coefficient
	Koc: Partition coefficient of organic carbon
	UFI: unique formula identifier
	IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at UK, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.